

FTXF-D / RXF-D



RXF-D

FTXF-D

Efficiency data		FTXF + RXF	20D + 20D	25D + 25D	35D + 35D	42D + 42D	50D + 50D	60D + 60D	71D + 71D		
Cooling capacity	Min./Nom./Max.	kW	1.3 /2.00 /2.4	1.3 /2.50 /2.8	1.3 /3.30 /3.8	1.4 /4.20 /4.3	1.70 /5.00 /6.00	1.70 /6.00 /7.00	2.30 /7.10 /7.30		
Heating capacity	Min./Nom./Max.	kW	1.30 /2.40 /3.30	1.30 /2.80 /3.70	1.30 /3.50 /4.40	1.40 /4.60 /5.00	1.70 /6.00 /7.70	1.70 /6.40 /8.00	2.30 /8.20 /9.00		
Power input	Cooling	Min./Nom./Max.	kW	0.31 /0.592 /0.72	0.31 /0.772 /1.05	0.31 /1.00 /1.40	0.31 /1.27 /1.50	-1.50 /-	-1.85 /-	-2.77 /-	
	Heating	Min./Nom./Max.	kW	0.25 /0.640 /0.95	0.25 /0.750 /1.11	0.25 /0.940 /1.50	0.25 /1.24 /1.40	-1.62 /-	-1.63 /-	-2.21 /-	
Space cooling	Energy efficiency class		A++						A		
	Capacity	Pdesign	kW	2.00	2.50	3.50	4.20	5.00	6.00	7.10	
	SEER		6.50						6.21	6.15	5.15
Annual energy consumption		kWh/a	108	135	188	226	282	342	483		
Space heating (Average climate)	Energy efficiency class		A+						A		
	Capacity	Pdesign	kW	2.20	2.40	2.60	3.30	4.60	4.80	6.20	
	SCOP/A		4.11						4.30	4.06	3.81
	Annual energy consumption		kWh/a	749	818	885	1,075	1,585	1,654	2,275	


Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. Data for high efficiency series, Eurovent certified | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. Data for standard efficiency series | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range

Indoor unit		FTXF	20D	25D	35D	42D	50D	60D	71D	
Dimensions	Unit	HeightxWidthxDepth	286 x770 x225				295 x990 x263			
Weight	Unit	kg	8.00		8.50	9.00	13.5			
Air filter	Type		Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m³/min	4.3 /6.0 /8 /9.8	4.3 /6.2 /8 /10.0	4.4 /6.4 /8 /11.5	4.9 /6.9 /9 /12.6	10.5 /11.9 /14.4 /16.8	10.7 /12.2 /14.8 /17.3
		Heating	Silent operation/ Low/Medium/ High	m³/min	5.3 /6.2 /8.3 /10.4	5.3 /6.4 /8.4 /10.4	5.3 /6.5 /8.6 /11.9	5.2 /6.7 /8.8 /12.8	10.7 /12.2 /14.8 /17.3	11.3 /12.8 /15.8 /17.9
Sound power level	Cooling	dBA	53.0		54.0	59.0	59	60	62	
	Heating	dBA	55.0		56.0	59.0	61	62		
Sound pressure level	Cooling	Silent operation/Low/High	dBA	20.0 /25.0 /39.0	20.0 /26.0 /40.0	20.0 /27.0 /43.0	22.0 /30.0 /45.0	31 /34 /43	33 /36 /45	34 /37 /46
	Heating	Silent operation/Low/High	dBA	21.0 /28.0 /39.0	21.0 /28.0 /40.0	21.0 /29.0 /40.0	22.0 /28.0 /44.0	30 /33 /42	32 /35 /44	33 /36 /45
Control systems	Infrared remote control		ARC470A1							
	Wired remote control		BRC073A1							
Piping connections Drain		18								

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 5m; level difference: 0m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m (horizontal) | See separate drawing for electrical data

Outdoor unit		RXF	20D	25D	35D	42D	50D	60D	71D	
Dimensions	Unit	HeightxWidthxDepth	550 x658 x275				734 x870 x373			
Weight	Unit	kg	24.0		28.0	46.0	50.0			
Sound power level	Cooling		-							
Sound pressure level	Cooling	Low/Nom./High	dBA	-/-/46.0		-/-/48.0		-/47 /-	-/49 /-	-/52 /-
	Heating	Low/Nom./High	dBA	-/-/47.0		-/-/48.0		-/49 /-	-/52 /-	
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10 ~48				
	Heating	Ambient	Min.~Max.	°CWB		-15 ~18				

Daikin Europe Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · <https://www.daikin.eu> · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

ECPEN22-050

01/2022

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

